

PREMIUM SILK EMULSION

Product Scope

Buxly Premium Silk Emulsion is a high quality acrylic emulsion. It has hiding powers and color retention properties. It is a low odor emulsion with high stain resistance, outstanding water resistance, anti-fungal properties, excellent coverage and outstanding washability. It is a premium quality decorative paint which gives an attractive silk luster.

Product Application

It is recommended to apply Buxly Premium Silk Emulsion by roller or spray only. For roller application dilute 20 – 30% with clean tap water by volume. For spray application dilute 30 – 40% with clean tap water by volume. Diluted paint must be mixed well before use. Do not leave the diluted paint for more than one day.

Packaging

Available in 4 and 18 liters pack sizes.

Technical Information

Type	Water Based Air Drying
Viscosity by STORMER Viscometer @ 25° C	100–120 KU
pH	8.5–9.5
Finish	Silky
Color	Assorted Colors
Application	Roller/Spray
Thinning Ratio for Application	(Paint 1 : Water ½) by volume (Depending upon the absorbency of the substrate)
Recommended no. of Coats	2–3 Coats
Surface Dry	1 Hour
Recoating	2 Hours
Covering	12–16m ² per Liter per coat (depending upon the absorbency of the substrate)
Shelf Life	18 months, if kept properly sealed within normal temperature