

WOOD SHIELD CLEAR LACQUER

Product Scope

Buxly Wood Shield Clear Lacquer is designed for use on wooden furniture, windows, doors, kitchen cabinets and other wooden structures. It must be applied over Buxly Wood Shield Sanding Sealer. Buxly Wood Shield Clear Lacquer imparts a prime class glossy finish to the substrate and helps protect the natural beauty of substrate. Buxly Wood Shield Clear Lacquer is not recommended for exterior use.

Product Application

Buxly Wood Shield Clear Lacquer is a blend of suitable resins with chosen additives which impart an extraordinary gloss, smoothness, film clarity, toughness, flexibility and moisture resistance to the product.

Packaging

Available in 1, 4 and 20 liters pack sizes.

Technical Information

Type of Product	Single Pack – Air Drying
Priming Coat	None
Finish	Matt – Semi-Gloss
Color	Milky White – Pale Yellow
Flash Point	≥10° C

Application Information

Application Method	Brush/Conventional Spray/Cloth Pad
Application Viscosity	Depends on method of application
Solvent/Cleaner	Buxly Wood Shield Thinner
Number of Coats	2-5 Coats (thin coats are recommended)
Surface Dry Time	05-10 Minutes
Hard Dry Time	20-30 Minutes
Over-Coat Time	1-2 Hours