

# BASECOAT SYNTHETIC UNDERCOAT

## Product Scope

Buxly Basecoat Synthetic Undercoat is an undercoat finish for wood and metal. It is also used as surfacer, applied by brush or spray. Its fast drying properties help job completion in shorter time and is also suitable for auto finishing jobs.

## Product Application

Buxly Basecoat Synthetic Undercoat is a multipurpose product which can be used as primer surface or undercoat on wooden and metal surfaces. It is very effective for smoothening out surface blemishes. It can be sanded and recoated to provide a smooth primed surface for overcoating.

## Technical Information

Type	Single Pack
Composition	Pigments and inert extenders in modified synthetic resin binder
Color	White/Off-White and Grey
Application	Brush/Spray
Drying Time	a) Surface Dry : 20 Minutes b) Recoat : After 1 – 2 Hours
Theoretical Spreading Rate	16 m <sup>2</sup> per Liter
Dry Film Thickness	25 microns
Coats Recommended	1-2 Coats
Finish	Smooth Matt
Volume Solids	40 ± 2 %
Topcoat	Buxly's A/D Synthetic Enamel
Thinner	Buxly's Mixing Thinner, Petrol or NC Thinner
Packing	3.64 and 20 Liters pack sizes
Storage Stability	One year when properly stored in original sealed container at 15 – 35°C