

BITUMINOUS PAINT BLACK

Product Scope

Buxly Bituminous Paint is based on special grades of bitumen and thinners. It has excellent corrosion resistance properties, an economical coating and gives very good adhesion to metals and plastered surfaces. All metal surfaces coated with Bituminous Paint Black will be protected from water, humidity and rusting.

Product Application

An ideal coating for drinking water tanks, water pipelines, electrical conduit pipelines, structural steel, iron sheets and fences etc. Also acts as waterproofing coat on cement works and R.C.C., wood can also be protected against termite and white ants by using bituminous solution. It is recommended to apply very thin coat on wood work.

Technical Information

Type	Single Pack
Composition	Special grades of bitumen and thinners
Colors	Black only
Application	Can be applied by spray or brush
Drying Time	a) Surface Dry : Within 6 Hours b) Hard Dry : Within 24 Hours
Average Spreading Rate	8-12 m ² per litre, depending on surface
Number of Coats	Minimum 2 recommended
Finish	Smooth, semi-gloss to glossy
Flexibility	Good
Adhesion to Concrete & Wood	Good
Weather Resistance	Excellent
Sunlight Resistance	Good
Water Resistance	Excellent
Packing	5 and 20 Litres pack sizes
Storage Stability	One year when stored properly in original sealed container at 15 to 35°C